

Elite Ultra Matt

Technical Data & Specification

Waterbased coating specifically developed for the restoration of mineral-board suspended ceilings.

Description

Premium quality coating for the restoration of suspended ceilings. Specially developed to offer a perfectly flat matt finish with excellent light reflectance. When applied over acoustic ceiling tiles, the acoustic properties and fire rating of the ceilings will remain intact.

Where to use

Suspended ceilings, acoustic ceiling tiles, mineral-board tiles, plaster and concrete. This coating is designed for interior ceiling applications. The flat matt finish eliminates the low angular sheen often exhibited by regular emulsions and the tiles will not stick to the grid.

Properties

- Ideal for suspended ceilings
- Waterbased
- Flat matt uniform finish
- Excellent productivity
- Non-Bridging (tiles will not stick to the grid system)
- B.S 476 Parts 6 & 7 (class '0' fire rating achieved)
- Vapour permeable
- Will not flake or peel

Preparation

Mask all light fittings, sprinkler heads, smoke detectors and tops of walls. Hang plastic sheeting down from tops of walls, continue the sheeting across floors & furniture until the area is totally protected from overspray. Brush down the surface to remove all dust, cobwebs, etc. and stainblock any waterstains.

Application

Apply by airless spray using a 0.15 tip. Dilute by 5% and apply one full coat overlapping each pass by 50%. This should be sufficient. However, depending on the substrate, a further mist coat may be required. Clean machine with warm water, remove masking & clean area ready for re-occupation.

Colour	White as standard but can be supplied in any pastel RAL or BS colour
Solids	62%
Spread rate	8m ² per litre depending on WFT Required.
Dry to touch	1 hour
Recoat after	2 hours
Clean up	Warm soapy water
Flash point	100°C
WFT	Up to 250 microns
Containers	15 litres
Weight	23 Kilos